



LITEFORM®



5029-14

LITEFORM® 5029-14

Features

Luminaire Dimensions 14" Diameter X 30.25" Height

Finial Cast aluminum

Lens Clear stippled polycarbonate, UV stabilized

Optical System - ML 5™ multi-louvre reflector system, specular finish, clear anodized aluminum
- REF5 borosilicate glass refractor

Ballast High power factor, magnetic, core & coil

Fitter Cast aluminum construction with Twist-Clamp™ quarter turn shade release system for ease of re-lamping and ballast maintenance

Lamp holder Medium base, porcelain, 4KV pulse-rated

Construction Aluminum throughout

Hardware Stainless steel

Fitter Tenon Mounts to 3.50" O.D. round post

Finish Polyester powder coat

Colours Black, Bronze, White, or Silver (*for custom colour consult factory*)

Luminaire Specification Guide

LITEFORM 5029-14	-	WATTAGE	-	VOLTAGE	-	OPTICAL SYSTEM	-	COLOUR
		70 HPS		120 V		ML5		BLACK
		100 HPS		347 V		REF5		BRONZE
		70 MH						WHITE
		100 MH						SILVER

Complete Assembly Specification Guide

LUMINAIRE - POLE - BASE - COLOUR

Example: LITEFORM 5029-14-100HPS-120V-REF5-FAR3510-R1188-BLACK



Liteform International Inc.
261 Ambassador Drive Mississauga, Ontario L5T 2J2
Canada Tel: (905) 564-2090 Fax: (905) 564-2102
www.liteformlighting.com