



LITEFORM®



5180

LITEFORM® 5180

Features

Luminaire Dimensions 16" Diameter X 24.75" Height

Lens Clear polycarbonate, UV stabilized, Faktor 10 coating

Optical System Cone reflector system, specular finish, clear anodized aluminum

Ballast High power factor, magnetic, core & coil

Fitter Cast aluminum construction with Twist-Clamp™ quarter turn shade release system for ease of re-lamping and ballast maintenance

Lamp holder Mogul base, porcelain, 4KV pulse-rated

Construction Aluminum throughout

Hardware Stainless steel

Fitter Tenon Mounts to 4.50" O.D. round post

Finish Polyester powder coat

Colours Black, Bronze, White, or Silver (*for custom colour consult factory*)

Luminaire Specification Guide

| LITEFORM 5180 | - | WATTAGE | - | VOLTAGE | - | COLOUR |
|---------------|---|---------|---|---------|---|--------|
| | | | | | | |
| | | 150 HPS | | 120 V | | BLACK |
| | | 250 HPS | | 347 V | | BRONZE |
| | | 175 MH | | | | WHITE |
| | | 250 MH | | | | SILVER |

Complete Assembly Specification Guide

LUMINAIRE - POLE - BASE - COLOUR

Example: LITEFORM 5180-150HPS-120V-SR4515-R1118-BLACK

(Note: for other wattages and voltages consult factory)



Liteform International Inc.
261 Ambassador Drive Mississauga, Ontario L5T 2J2
Canada Tel: (905) 564-2090 Fax: (905) 564-2102
www.liteformlighting.com